



- High power
- Low noise
- Compact design
- Easy installation
- Program timer
- Auto-restart
- Automatic air flow adjustment
- Washable air filter



For ARY12L/14L/18L

Fujitsu's new duct type air conditioning system offers quiet, efficient operation as either ceiling-mounted or floor-mounted units. The compact design of the units allows for easy installation and makes them ideal for situations where space is at a premium. Adjustable via wired remote control, the new duct type units also feature automatic air flow adjustment.



Optional parts



Remote Sensor Simple Remote Wireless controller Receiver unit

		Inverter Heat Pump - R410A			
		Indoor	ARY12L	ARY14L	ARY18L
		Outdoor	AOY12L	AOY14L	AOY18L
Auto Air Flow Adjustment			✓	✓	✓
Auto Restart			✓	✓	✓
Program Timer			✓	✓	✓
Auto-Changeover			✓	✓	✓
Weekly Timer			✓	✓	✓
Weekly + Setback Timer			✓	✓	✓
Nominal Capacity (kW)	Cooling		3.50	4.20	5.20
	Heating		4.00	4.80	6.20
Moisture Removal	l/h		1.20	1.50	1.70
Dimensions (HxWxD) mm	Indoor		217x953x595	217x953x595	217x953x595
	Outdoor		650x830x320	650x830x320	650x830x320
Net Weight (kg)	Indoor		25	25	25
	Outdoor		54	54	54
Room Air Circulation (high) m ³ /h	Inner		580	780	800
	Outer		2800	2800	2800
Power Supply	V-PH-Hz		230 / 1 / 50	230 / 1 / 50	230 / 1 / 50
Power Supply To			Outdoor	Outdoor	Outdoor
Running Current (A)	Cooling		5.10	6.00	7.40
	Heating		5.70	6.50	8.30
Starting Current	A		10	10	10
Fuse Rating	A		15	15	20
Power Consumption (kW)	Cooling		1.15	1.37	1.70
	Heating		1.30	1.49	1.90
Interconnecting Cable			3 + E	3 + E	3 + E
Remote Control Type			Wired	Wired	Wired
Noise Levels (dB(A))	Indoor L/M/H		28 / 31 / 34	31 / 36 / 40	30 / 34 / 38
	Outdoor		49	49	50
Max Pipe Length	m		25	25	25
Max Height Difference	m		15	15	15
Refrigerant Charge	m		10	10	10
Static Pressure	Pa		0 (Max. 40)	0 (Max. 40)	0 (Max. 40)
Pipe Size (inches)	Gas		3/8 (9.52mm)	1/2 (12.70mm)	1/2 (12.70mm)
	Liquid		1/4 (6.35mm)	1/4 (6.35mm)	1/4 (6.35mm)
Operating Range (°C)	Cooling		10 ~ 43	10 ~ 43	0 ~ 43
	Heating		-10 ~ 24	-10 ~ 24	-10 ~ 24
Refrigerant			R410A	R410A	R410A

Cooling & Heating capacities are based on the following conditions:

Cooling: Indoor Temp.: 27°C DB/19°C WB, Outdoor Temp.: 35°C DB/24°C WB

Heating: Indoor Temp.: 20°C DB, Outdoor Temp.: 7°C DB

Note: Fuse ratings shown are only for information. Any fuses or MCB's installed on-site should be sized in accordance with I.E.E. regulations.

For full installation details please contact your local distributor

Distributed by:



ISO 9001:2000 Certified number 100 80206 Fujitsu General (Thailand) Co., Ltd.
 ISO 14001:2004 Certified number 100 80104 Fujitsu General (Thailand) Co., Ltd.
 ISO 9001:2000 Certified number 100 70203 Fujitsu General (Shanghai) Co., Ltd.
 ISO 14001:2004 Certified number 100802 Fujitsu General (Shanghai) Co., Ltd.

The company reserves the right to make any variation in specification to the equipment described or to withdraw or replace products without prior notification or public announcement. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form any part of any contract. For full installation details please contact your local distributor.



- High power
- Low noise
- Compact design
- Easy installation
- Program timer
- Auto-restart
- Automatic air flow adjustment
- Washable air filter



For ARY12L/14L/18L

Fujitsu's new duct type air conditioning system offers quiet, efficient operation as either ceiling-mounted or floor-mounted units. The compact design of the units allows for easy installation and makes them ideal for situations where space is at a premium. Adjustable via wired remote control, the new duct type units also feature automatic air flow adjustment.



Optional parts



Remote Sensor Simple Remote Wireless controller Receiver unit

		Inverter Heat Pump - R410A			
		Indoor	ARY12L	ARY14L	ARY18L
		Outdoor	AOY12L	AOY14L	AOY18L
Auto Air Flow Adjustment			✓	✓	✓
Auto Restart			✓	✓	✓
Program Timer			✓	✓	✓
Auto-Changeover			✓	✓	✓
Weekly Timer			✓	✓	✓
Weekly + Setback Timer			✓	✓	✓
Nominal Capacity (kW)	Cooling		3.50	4.20	5.20
	Heating		4.00	4.80	6.20
Moisture Removal	l/h		1.20	1.50	1.70
Dimensions (HxWxD) mm	Indoor		217x953x595	217x953x595	217x953x595
	Outdoor		650x830x320	650x830x320	650x830x320
Net Weight (kg)	Indoor		25	25	25
	Outdoor		54	54	54
Room Air Circulation (high) m ³ /h	Inner		580	780	800
	Outer		2800	2800	2800
Power Supply	V-PH-Hz		230 / 1 / 50	230 / 1 / 50	230 / 1 / 50
Power Supply To			Outdoor	Outdoor	Outdoor
Running Current (A)	Cooling		5.10	6.00	7.40
	Heating		5.70	6.50	8.30
Starting Current	A		10	10	10
Fuse Rating	A		15	15	20
Power Consumption (kW)	Cooling		1.15	1.37	1.70
	Heating		1.30	1.49	1.90
Interconnecting Cable			3 + E	3 + E	3 + E
Remote Control Type			Wired	Wired	Wired
Noise Levels (dB(A))	Indoor L/M/H		28 / 31 / 34	31 / 36 / 40	30 / 34 / 38
	Outdoor		49	49	50
Max Pipe Length	m		25	25	25
Max Height Difference	m		15	15	15
Refrigerant Charge	m		10	10	10
Static Pressure	Pa		0 (Max. 40)	0 (Max. 40)	0 (Max. 40)
Pipe Size (inches)	Gas		3/8 (9.52mm)	1/2 (12.70mm)	1/2 (12.70mm)
	Liquid		1/4 (6.35mm)	1/4 (6.35mm)	1/4 (6.35mm)
Operating Range (°C)	Cooling		10 ~ 43	10 ~ 43	0 ~ 43
	Heating		-10 ~ 24	-10 ~ 24	-10 ~ 24
Refrigerant			R410A	R410A	R410A

Cooling & Heating capacities are based on the following conditions:

Cooling: Indoor Temp.: 27°C DB/19°C WB, Outdoor Temp.: 35°C DB/24°C WB

Heating: Indoor Temp.: 20°C DB, Outdoor Temp.: 7°C DB

Note: Fuse ratings shown are only for information. Any fuses or MCB's installed on-site should be sized in accordance with I.E.E. regulations.

For full installation details please contact your local distributor

Distributed by:



ISO 9001:2000 Certified number: 028 100 80206
 ISO 14001:2004 Certified number: 028 100 80140
 Fujitsu General (Thailand) Co., Ltd.

ISO 9001:2000 Certified number: 028 100 70208
 ISO 14001:2004 Certified number: 028 100 70209
 Fujitsu General (Shanghai) Co., Ltd.

The company reserves the right to make any variation in specification to the equipment described or to withdraw or replace products without prior notification or public announcement. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form any part of any contract. For full installation details please contact your local distributor.